

107.1 - Primary Gas Mixtures

These SRMs are for calibrating equipment and apparatus used to measure various components of gas mixtures and atmospheric pollutants. The typical gas mixture is supplied in a DOT 3AL specification aluminum (6061 alloy) cylinder with a nominal pressure exceeding 12.4 mPa that provides the user with approximately 0.73m3 of usable mixture. Due to increasing customer demand, these primary gas mixtures are in short supply and may not be readily available for sale. In such cases, a NIST traceable reference gas described below may be substituted.

A NIST Traceable Reference Material (NTRM) is a reference material produced by a commercial supplier with a well-defined traceability to NIST. This traceability is established via criteria and protocols defined by NIST that are tailored to meet the needs of the metrological community to be served. The NTRM concept was established to allow NIST to respond to the increasing needs for high quality reference materials by leveraging its relatively fixed human and financial resources with secondary reference material producers. Reference material producers adhering to NIST defined protocol requirements are allowed to use the NTRM trademark to identify their product.

The gas NTRM program was established in 1992 in partnership with the U.S. EPA and specialty gas companies as a means for providing end-users with the wide variety of certified gas standards needed to implement the Emissions Trading provision of the 1990 Clean Air Act. Gas NTRMs are produced and distributed by specialty gas companies with NIST oversight of the production and maintenance, and direct involvement in the analysis. NTRMs can be developed for any pollutant, concentration, and balance gas combination for which a NIST primary standard or SRM exists. The gas standards prepared according to this program are related, within known limits of uncertainty, to specific gaseous primary standards maintained by NIST.

Technical Contact: [franklin.guenther@nist.gov](mailto:franklin.guenther@nist.gov).

PLEASE NOTE: The tables are presented to facilitate comparisons among a family of materials to help customers select the best SRM for their needs. For specific values and uncertainties, the certificate is the only official source.

SRM	1658a	1659a	1660a	1661a*	1662a*	1663a*	1664a*	1665b	1666b	1667b	1668b*	1669b	1674b*	1676	1677c*	1678c*	1679c*	1680b*	1681b*	1683b*
Description	Methane in Air (Nominal 1 umol/mol)	Methane in Air (Nominal 10 umol/mol)	Methane and Propane in Air (Nominal: Methane 4 umol/mol; Propane 1 umol/mol)	Sulfur Dioxide in Nitrogen (Nominal 500 umol/mol)	Sulfur Dioxide in Nitrogen (Nominal 1000 umol/mol)	Sulfur Dioxide in Nitrogen (Nominal 1500 umol/mol)	Sulfur Dioxide in Nitrogen (Nominal 2500 umol/mol)	Propane in Air (Nominal 3 umol/mol)	Propane in Air (Nominal 10 umol/mol)	Propane in Air (Nominal 50 umol/mol)	Propane in Air (Nominal 100 umol/mol)	Propane in Air (Nominal 500 umol/mol)	Carbon Dioxide in Nitrogen (Nominal 7 %)	Carbon Dioxide in Air (Nominal 365 umol/mol)	Carbon Monoxide in Nitrogen (Nominal 10 umol/mol)	Carbon Monoxide in Nitrogen (Nominal 50 umol/mol)	Carbon Monoxide in Nitrogen (Nominal 100 umol/mol)	Carbon Monoxide in Nitrogen (Nominal 500 umol/mol)	Carbon Monoxide in Nitrogen (Nominal 1000 umol/mol)	Nitric Oxide in Nitrogen (Nominal 50 umol/mol)
Unit of Issue	(cylinder)	(cylinder)	(cylinder)	(cylinder)	(cylinder)	(cylinder)	(cylinder)	(cylinder)	(cylinder)	(cylinder)	(cylinder)	(cylinder)	(cylinder)	(cylinder)	(cylinder)	(cylinder)	(cylinder)	(cylinder)	(cylinder)	(cylinder)

Certified Component	1	CH <sub>4</sub>	CH <sub>4</sub> : C <sub>3</sub> H <sub>8</sub>	SO <sub>2</sub>	SO <sub>2</sub>	SO <sub>2</sub>	SO <sub>2</sub>	C <sub>3</sub> H <sub>8</sub>	C <sub>3</sub> H <sub>8</sub>	C <sub>3</sub> H <sub>8</sub>	C <sub>3</sub> H <sub>8</sub>	C <sub>3</sub> H <sub>8</sub>	CO <sub>2</sub>	CO <sub>2</sub>	CO	CO	CO	CO	CO	NO
Nominal Amount-of-substance fraction	CH <sub>4</sub>	10 umol/mol	4:1 umol/mol	500 umol/mol	1000 umol/mol	1500 umol/mol	2500 umol/mol	3 umol/mol	10 umol/mol	50 umol/mol	100 umol/mol	500 umol/mol	7 % mol/mol	365 umol/mol	10 umol/mol	50 umol/mol	100 umol/mol	500 umol/mol	1000 umol/mol	50 umol/mol

\* Those SRMs that are marked "\*" are available as [NTRMs](#), from commercial suppliers.

107.1 - Primary Gas Mixtures

These SRMs are for calibrating equipment and apparatus used to measure various components of gas mixtures and atmospheric pollutants. The typical gas mixture is supplied in a DOT 3AL specification aluminum (6061 alloy) cylinder with a nominal pressure exceeding 12.4 mPa that provides the user with approximately 0.73m3 of usable mixture. Due to increasing customer demand, these primary gas mixtures are in short supply and may not be readily available for sale. In such cases, a NIST traceable reference gas described below may be substituted.

A NIST Traceable Reference Material (NTRM) is a reference material produced by a commercial supplier with a well-defined traceability to NIST. This traceability is established via criteria and protocols defined by NIST that are tailored to meet the needs of the metrological community to be served. The NTRM concept was established to allow NIST to respond to the increasing needs for high quality reference materials by leveraging its relatively fixed human and financial resources with secondary reference material producers. Reference material producers adhering to NIST defined protocol requirements are allowed to use the NTRM trademark to identify their product.

The gas NTRM program was established in 1992 in partnership with the U.S. EPA and specialty gas companies as a means for providing end-users with the wide variety of certified gas standards needed to implement the Emissions Trading provision of the 1990 Clean Air Act. Gas NTRMs are produced and distributed by specialty gas companies with NIST oversight of the production and maintenance, and direct involvement in the analysis. NTRMs can be developed for any pollutant, concentration, and balance gas combination for which a NIST primary standard or SRM exists. The gas standards prepared according to this program are related, within known limits of uncertainty, to specific gaseous primary standards maintained by NIST.

Technical Contact: [franklin.guenther@nist.gov](mailto:franklin.guenther@nist.gov).

PLEASE NOTE: The tables are presented to facilitate comparisons among a family of materials to help customers select the best SRM for their needs. For specific values and uncertainties, the certificate is the only official source.

SRM	1684b*	1685b*	1686b*	1687b*	1693a*	1694a*	1696a*	1800b	1804c	2612a	2613a	2614a	2617	2619a	2620a	2621a	2622a	2623a	2624a	2625a*
Description	Nitric Oxide in Nitrogen (Nominal 100 μmol/mol)	Nitric Oxide in Nitrogen (Nominal 250 μmol/mol)	Nitric Oxide in Nitrogen (Nominal 500 μmol/mol)	Nitric Oxide in Nitrogen (Nominal 1000 μmol/mol)	Sulfur in Nitrogen (Nominal 50 μmol/mol)	Sulfur Dioxide in Nitrogen (Nominal 100 μmol/mol)	Sulfur Dioxide in Nitrogen (Nominal 3500 μmol/mol)	Eighteen Non-Methane Hydrocarbon Compounds in Nitrogen (Nominal 5 nmol/mol)	Toxic Volatile Organic Compounds in Nitrogen (Nominal 5.0 nmol/mol)	Carbon Monoxide in Air (Nominal 10 μmol/mol)	Carbon Monoxide in Air (Nominal 20 μmol/mol)	Carbon Monoxide in Air (Nominal 42 μmol/mol)	Carbon Dioxide in Nitrogen (Nominal 500 μmol/mol)	Carbon Dioxide in Nitrogen (Nominal 0.5 % mol/mol)	Carbon Dioxide in Nitrogen (Nominal 1.0 % mol/mol)	Carbon Dioxide in Nitrogen (Nominal 1.5 % mol/mol)	Carbon Dioxide in Nitrogen (Nominal 2.0 % mol/mol)	Carbon Dioxide in Nitrogen (Nominal 2.5 % mol/mol)	Carbon Dioxide in Nitrogen (Nominal 3.0 % mol/mol)	Carbon Dioxide in Nitrogen (Nominal 3.5 % mol/mol)
Unit of Issue	(cylinder)	(cylinder)	(cylinder)	(cylinder)	(cylinder)	(cylinder)	(cylinder)	(6 L Water Volume Cyl)	(cylinder)	(cylinder)	(cylinder)	(cylinder)	(cylinder)	(cylinder)	(cylinder)	(cylinder)	(cylinder)	(cylinder)	(cylinder)	(cylinder)

Certified Component	NO	NO	NO	NO	SO <sub>2</sub>	SO <sub>2</sub>	SO <sub>2</sub>	(Eighteen components in small cylinder)	(Thirty components)	CO	CO	CO	CO <sub>2</sub>	CO <sub>2</sub>	CO <sub>2</sub>	CO <sub>2</sub>	CO <sub>2</sub>	CO <sub>2</sub>	CO <sub>2</sub>	CO <sub>2</sub>
Nominal Amount-of-substance fraction	100 μmol/mol	250 μmol/mol	500 μmol/mol	1000 μmol/mol	50 μmol/mol	100 μmol/mol	3500 μmol/mol	5 nmol/mol	5 nmol/mol	10 μmol/mol	20 μmol/mol	42 μmol/mol	500 μmol/mol	0.5 % mol/mol	1.0 % mol/mol	1.5 % mol/mol	2.0 % mol/mol	2.5 % mol/mol	3.0 % mol/mol	3.5 % mol/mol

\* Those SRMs that are marked "\*" are available as [NTRMs](#) from commercial suppliers.

107.1 - Primary Gas Mixtures

These SRMs are for calibrating equipment and apparatus used to measure various components of gas mixtures and atmospheric pollutants. The typical gas mixture is supplied in a DOT 3AL specification aluminum (6061 alloy) cylinder with a nominal pressure exceeding 12.4 mPa that provides the user with approximately 0.73m3 of usable mixture. Due to increasing customer demand, these primary gas mixtures are in short supply and may not be readily available for sale. In such cases, a NIST traceable reference gas described below may be substituted.

A NIST Traceable Reference Material (NTRM) is a reference material produced by a commercial supplier with a well-defined traceability to NIST. This traceability is established via criteria and protocols defined by NIST that are tailored to meet the needs of the metrological community to be served. The NTRM concept was established to allow NIST to respond to the increasing needs for high quality reference materials by leveraging its relatively fixed human and financial resources with secondary reference material producers. Reference material producers adhering to NIST defined protocol requirements are allowed to use the NTRM trademark to identify their product.

The gas NTRM program was established in 1992 in partnership with the U.S. EPA and specialty gas companies as a means for providing end-users with the wide variety of certified gas standards needed to implement the Emissions Trading provision of the 1990 Clean Air Act. Gas NTRMs are produced and distributed by specialty gas companies with NIST oversight of the production and maintenance, and direct involvement in the analysis. NTRMs can be developed for any pollutant, concentration, and balance gas combination for which a NIST primary standard or SRM exists. The gas standards prepared according to this program are related, within known limits of uncertainty, to specific gaseous primary standards maintained by NIST.

Technical Contact: [franklin.guenther@nist.gov](mailto:franklin.guenther@nist.gov).

PLEASE NOTE: The tables are presented to facilitate comparisons among a family of materials to help customers select the best SRM for their needs. For specific values and uncertainties, the certificate is the only official source.

SRM	2627a	2628a	2629a*	2630*	2631a*	2635a*	2636a*	2637a*	2638a*	2639a	2640a	2641a	2642a*	2644a	2646a	2647a	2657a*	2658a*	2659a*	2660a*
Description	Nitric Oxide in Nitrogen (Nominal 5 μmol/mol)	Nitric Oxide in Nitrogen (Nominal 10 μmol/mol)	Nitric Oxide in Nitrogen (Nominal 20 μmol/mol)	Nitric Oxide in Nitrogen (Nominal 1500 μmol/mol)	Nitric Oxide in Nitrogen (Nominal 3000 μmol/mol)	Carbon Monoxide in Nitrogen (Nominal 25 μmol/mol)	Carbon Monoxide in Nitrogen (Nominal 250 μmol/mol)	Carbon Monoxide in Nitrogen (Nominal 2500 μmol/mol)	Carbon Monoxide in Nitrogen (Nominal 5000 μmol/mol)	Carbon Monoxide in Nitrogen (Nominal 1 % mol/mol)	Carbon Monoxide in Nitrogen (Nominal 2 % mol/mol)	Carbon Monoxide in Nitrogen (Nominal 4 % mol/mol)	Carbon Monoxide in Nitrogen (Nominal 8 % mol/mol)	Propane in Nitrogen (Nominal 250 μmol/mol)	Propane in Nitrogen (Nominal 1000 μmol/mol)	Propane in Nitrogen (Nominal 2500 μmol/mol)	Oxygen in Nitrogen (Nominal 2 % mol/mol)	Oxygen in Nitrogen (Nominal 10 % mol/mol)	Oxygen in Nitrogen (Nominal 21 % mol/mol)	Total Oxides of Nitrogen (NOx) in Air (Nominal 100 μmol/mol)
Unit of Issue	(cylinder)	(cylinder)	(each)	(each)	(cylinder)	(cylinder)	(cylinder)	(cylinder)	(cylinder)	(cylinder)	(cylinder)	(cylinder)	(cylinder)	(cylinder)	(cylinder)	(cylinder)	(cylinder)	(cylinder)	(cylinder)	(cylinder)
Certified Component	NO	NO	NO	NO	NO	CO	CO	CO	CO	CO	CO	CO	CO	C3H8	C3H8	C3H8	O2	O2	O2	NOx
Nominal Amount-of-substance fraction	5 μmol/mol	10 μmol/mol	20 μmol/mol	1500 μmol/mol	3000 μmol/mol		250 μmol/mol	2500 μmol/mol	5000 μmol/mol	1 % mol/mol	2 % mol/mol	4 % mol/mol	8 % mol/mol	250 μmol/mol	1000 μmol/mol	2500 μmol/mol	2 % mol/mol	10 % mol/mol	21 % mol/mol	100 μmol/mol

\* Those SRMs that are marked "\*" are available as [NTRMs](#) from commercial suppliers.

107.1 - Primary Gas Mixtures

These SRMs are for calibrating equipment and apparatus used to measure various components of gas mixtures and atmospheric pollutants. The typical gas mixture is supplied in a DOT 3AL specification aluminum (6061 alloy) cylinder with a nominal pressure exceeding 12.4 mPa that provides the user with approximately 0.73m3 of usable mixture. Due to increasing customer demand, these primary gas mixtures are in short supply and may not be readily available for sale. In such cases, a NIST traceable reference gas described below may be substituted.

A NIST Traceable Reference Material (NTRM) is a reference material produced by a commercial supplier with a well-defined traceability to NIST. This traceability is established via criteria and protocols defined by NIST that are tailored to meet the needs of the metrological community to be served. The NTRM concept was established to allow NIST to respond to the increasing needs for high quality reference materials by leveraging its relatively fixed human and financial resources with secondary reference material producers. Reference material producers adhering to NIST defined protocol requirements are allowed to use the NTRM trademark to identify their product.

The gas NTRM program was established in 1992 in partnership with the U.S. EPA and specialty gas companies as a means for providing end-users with the wide variety of certified gas standards needed to implement the Emissions Trading provision of the 1990 Clean Air Act. Gas NTRMs are produced and distributed by specialty gas companies with NIST oversight of the production and maintenance, and direct involvement in the analysis. NTRMs can be developed for any pollutant, concentration, and balance gas combination for which a NIST primary standard or SRM exists. The gas standards prepared according to this program are related, within known limits of uncertainty, to specific gaseous primary standards maintained by NIST.

Technical Contact: [franklin.guenther@nist.gov](mailto:franklin.guenther@nist.gov).

PLEASE NOTE: The tables are presented to facilitate comparisons among a family of materials to help customers select the best SRM for their needs. For specific values and uncertainties, the certificate is the only official source.

SRM	2730	2731	2735	2737	2738	2740a	2741a	2745*	2750	2751	2764	2765
Description	Hydrogen Sulfide in Nitrogen (Nominal 5	Hydrogen Sulfide in Nitrogen (Nominal 20	Nitric Oxide in Nitrogen (Nominal 800	Nitric Oxide in Nitrogen (Nominal 500	Nitric Oxide in Nitrogen (Nominal 1000	Carbon Monoxide in Nitrogen (Nominal 10 %	Carbon Monoxide in Nitrogen (Nominal 13 %	Carbon Dioxide in Nitrogen (Nominal 16 %	Methane in Air (Nominal 50	Methane in Air (Nominal 100	Propane in Air (Nominal 0.25	Propane in Air (Nominal 100
Unit of Issue	μmol/mol (cylinder)	μmol/mol (cylinder)	μmol/mol (cylinder)	nmol/mol (cylinder)	nmol/mol (cylinder)	mol/mol (cylinder)	mol/mol (cylinder)	mol/mol (cylinder)	μmol/mol (cylinder)	μmol/mol (cylinder)	μmol/mol (cylinder)	nmol/mol (cylinder)

Certified Component	H <sub>2</sub> S	H <sub>2</sub> S	NO	NO	NO	CO	CO	CO <sub>2</sub>	CH <sub>4</sub>	CH <sub>4</sub>	C <sub>3</sub> H <sub>8</sub>	C <sub>3</sub> H <sub>8</sub>
Nominal Amount-of-substance fraction	5 μmol/mol	20 μmol/mol	800 μmol/mol	500 μmol/mol	1000 μmol/mol	10 % mol/mol	13 % mol/mol	16 % mol/mol	50 μmol/mol	100 μmol/mol	0.25 μmol/mol	100 nmol/mol

\* Those SRMs that are marked "\*" are available as [NTRMs](#) from commercial suppliers.